

## SEN-IDF20 (2.0MP)



### Features

- H.264 & MJPEG HD Network Camera
- Dual Stream
- 2MP (1080P) @ 30FPS
- PoE 802.3af Class 2
- Auto Focus for Easy Installation
- Motion Triggered Alarm
- Multi Language GUI support
- Contrast Enhancement
- ONVIF Compliant
- f 2.1mm Fixed Lens
- 2D/3D DNR

MODEL	SEN-IDF20
<b>CAMERA</b>	
Image Sensor	1/2.8" Sony IMX-036 CMOS Sensor
Max. Resolution	1920 x 1080
Effective Pixels	2096(H) x 1561(V)
Effective Image Size	5.24mm(H) x 3.90mm(V), 6.53mm(Diagonal)
White Balance	ATW / MANUAL(PRESET)
Electronic Zoom	2 ~ 10x(Client Software)
AGC	Yes
BLC	Yes
Iris	No
Shutter Speed	1/4, 1/10, 1/12.5, 1/15, 1/20, 1/25, 1/30, 1/50, 1/60, 1/100, 1/120, 1/240, 1/480, 1/960, 1/1024, 1/2000 s(TBD)
Slow Shutter	TBD
Lens	Board Mount. f 2.1mm Fixed Megapixel Lens
Day & Night	Digital Day & Night
S/N ratio	50 dB or more
Min. illumination	Color: 0.7 lux(F1.2, 30IRE) B/W: 0.08 lux(F1.2, Slow Shutter ON, 30IRE)
<b>NETWORK</b>	
Network	10BASE-T, 100BASE-TX, RJ45
	H.264 : Main Profile
Image Compression	MJPEG - Image quality: 5 Steps: Lowest, Low : Medium: High, Highest
Resolution	1920 x 1080(Full HD), 1280 x 1024(SXGA), 1024 x 768(XGA), 1280 x 720(720p) 640 x 480(VGA), 320 x 240(QVGA) 704 x 480/576(4CIF), 352 x 240/288(CIF)
Protocol	IPv4/6, HTTP, HTTPS, SMTP, UPnP, DNS, DynamicDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP
Frame Rate	1 fps ~ 25 fps / 1 fps ~ 30 fps
Web Browser	Internet Explorer 7.0 or above, Firefox, Chrome, PDA/Smart phone
Security	Password Protection, HTTPS, IP Addressing Filtering
SDK(API)	HTML based API
VMD(Video Motion Detection)	User set 4 ROI(Region Of Interest) / 10 Step Sensitivity
Alarm Trigger	VMD
Alarm Event	E-mail notification, FTP transfer, Video stream with alarm status, Post Alarm
<b>POWER</b>	
Power Source	PoE(IEEE 802.3af compliant)
Power Consumption	100mA @ DC48V, Max 4.8W (TBD)
<b>OTHER SPECIFICATIONS</b>	
Ambient Temperature	-10°C ~ 50°C(14°F~122°F)
Ambient Humidity	less than 90%, Non-condensing
Materials	Aluminum Diecasting
Weight	360g
Dimensions(W x H x D)	110(Φ)x67.5(H)

Made in Korea

### Dimensions

(unit:mm)

