



1080p HD-SDI DVR

High Definition Video over Coaxial Cables

ADVANCED FEATURES

- 1080p Full HD Real-time Video Recording
- High Definition Display with HDMI
- H.264 Video Format
- DVD Writer for Video Backup
- Up to 8 TB Internal Storage
- Dual Streaming
- Easy-to-Use Graphical User Interface
- 1080p Full HD Real-time Live Video
- HD Video over Existing Coaxial Cables
- Smart Phone Apps
- Covert Camera Operation
- Motion based Smart Search
- Thumbnail Search
- Powerful CMS Program

HISCO WINDOWS BASED HD DVR SPECIFICATIONS

Model	HIS-HD1204	HIS-HD2408	HIS-HD4816	
VIDEO	Video Input	4 HD-SDI	8 HD-SDI	16 HD-SDI
	Video Output	1 VGA, 1 HDMI	1 VGA, 1 HDMI	1 VGA, 1 HDMI
	Spot Monitor	N/A	N/A	N/A
	Display Resolution	MAX. 1920X1080	MAX. 1920X1080	MAX. 1920X1080
RECORD & PLAYBACK	Video Compression	H.264		
	Live Display Speed	Real-Time		
	Recording Rate	120 @ 1080p	240 @ 1080p	480 @ 1080p
	Recording Mode	Continuous, Motion, Sensor, Motion & Sensor, Normal & Event		
	Playback Mode	Timeline, Index, Date & Time, Event, Smart Search, Quick Search		
	Playback Speed	X1, X2, X4, X8, X16, X32, X64		
	Archive File Format	AVI (Video Clip) / JPEG (Still Image)		
SYSTEM	Operating System	WINDOWS 7		
	Backup Device	DVD+/-RW		
	Storage	40GB SSD for O/S Drive, 1 TB for Video Storage (Expandable to 8TB)		
	Video Export	USB, CD/DVD RW, Network		
NETWORK	Connection	Ethernet		
	Protocol	LAN, DHCP, DDNS,		
	Remote Connection	CMS, Smart Phone App (iPhone, Android), IE		
INTERFACE	Audio In (Optional)	2	2	2
	Alarm In / Out	Optional 4 In/ 4 Out	Optional 8 In/ 8 Out	Optional 16 In/ 16 Out
	PTZ CONTROL	Optional RS-485/422		
	USB Interface	10 Ports (2 x Front Panel, 8 x Rear Panel)		
REMOTE ACCESS	Web Setting	Live Monitoring, Search, Setup, Backup		
	Covert Camera	Local/Remote		
ETC	Dimension (W x H x D)	430 x 170 x 425(mm)		
	Operating Temperature	5°C ~ 40°C		
	Power	100V ~ 240V AC, 50-60 Hz		
	Operating Humidity	10 ~ 90%		