



1080p HD-SDI Hybrid DVR

Upto 8 HD and 16 Analogue Cameras

ADVANCED FEATURES

- 1080p Full HD Real-time Video Recording
- Hybrid: Upto 8 HD & 16 Analogue Video
- H.264 Video Format
- DVD Writer for Video Backup
- Up to 8 TB Internal Storage
- Dual Streaming
- Easy-to-Use Graphical User Interface
- 1080p Full HD Real-time Live Video
- HD Video over Existing Coaxial Cables
- Smart Phone Apps
- Covert Camera Operation
- Motion based Smart Search
- Thumbnail Search
- Powerful CMS Program

HISCO WINDOWS BASED HD DVR SPECIFICATIONS

Model	HIS-HD4820	HIS-HD4824	
VIDEO	Video Input	4 HD-SDI & 16 Analogue	8 HD-SDI & 16 Analogue
	Video Output	1 VGA, 1 HDMI	1 VGA, 1 HDMI
	Spot Monitor	2 for Analogue Cameras	2 for Analogue Cameras
	Display Resolution	MAX. 1920X1080	MAX. 1920X1080
RECORD & PLAYBACK	Video Compression	H.264	
	Live Display Speed	Real-time	Real-time
	Recording Rate	120 @ 1080p(HD) & 480 @ D1(SD)	240 @ 1080p(HD) & 480 @ D1(SD)
	Recording Mode	Continuous, Motion, Sensor, Motion & Sensor, Normal & Event	
	Playback Mode	Timeline, Index, Date & Time, Event, Smart Search, Quick Search	
	Playback Speed	X1, X2, X4, X8, X16, X32, X64	
	Archive File Format	AVI (Video Clip) / JPEG (Still Image)	
SYSTEM	Operating System	WINDOWS 7	
	Backup Device	DVD+/-RW	
	Storage	40GB SSD for O/S Drive, 1 TB for Video Storage (Expandable to 8TB)	
	Video Export	USB, CD/DVD RW, Network	
NETWORK	Connection	Ethernet	
	Protocol	LAN, DHCP, DDNS,	
	Remote Connection	CMS, Smart Phone App (iPhone, Android), IE	
INTERFACE	Audio In (Optional)	2	2
	Alarm In / Out	Optional 4 In/ 4 Out	Optional 8 In/ 8 Out
	PTZ CONTROL	Optional RS-485/422	
	USB Interface	10 Ports (2 x Front Panel, 8 x Rear Panel)	
REMOTE ACCESS	Web Setting	Live Monitoring, Search, Setup, Backup	
	Covert Camera	Local/Remote	
ETC	Dimension (W x H x D)	430 x 170 x 425(mm)	
	Operating Temperature	5°C ~ 40°C	
	Power	100V ~ 240V AC, 50-60 Hz	
	Operating Humidity	10 ~ 90%	