



**REAL-TIME RECORDING**



HIS-SEN8DH



HIS-SEN16DH

## ADVANCED FEATURES

- High Quality H.264 Real-Time Video Recording
- High Definition Display with HDMI(1920 x 1080)
- Instant Playback while Live Viewing
- Real-time Log Viewer
- Support for RAID 1 (Morroring)
- Dual Streaming
- Up to 16 Cameras Simultaneous Playback
- iPhone, iPad and Android Phone Apps
- Free DDNS
- Auto Port Forwarding by UPnP
- Video Book Mark for Quick Archiving
- Email Notification with JPG Image (1ch)
- Jog Shuttle
- Overwrite Protection for Critical Video

## HISCO SENTINEL **DH** SERIES DVR SPECIFICATIONS

Model	HIS-SEN8DH	HIS-SEN16DH	
<b>VIDEO</b>	Video Input	8CH(BNC)	16CH(BNC)
	Ouput	1 BNC, 1 VGA, 8 Loop Outs, 1 HDMI, 1 S-Video 2 Analogue SPOT	1 BNC, 1 VGA, 16 Loop Outs, 1 HDMI, 1 S-Video, 4 Analogue SPOT
	Display Resolution	HDMI (MAX. 1920X1080) VGA (1 SXGA. 1280 X1024)	HDMI (MAX. 1920X1080) VGA (1 SXGA. 1280 X1024)
<b>RECORD &amp; PLAYBACK</b>	Video Compression	H.264 (DSP Based)	
	Live Display Speed	240 fps	480 fps
	Recording Rate	240 fps @ D1	480 fps @ D1
	Recording Mode	Continuous, Event, Pre-Event (upto 5sec), Panic	
	Recording Quality	Independent channel setting: resolution, quality, frame rate	
Search Mode	Date/Time, Calender, Event, Multi-Zone hour		
<b>SYSTEM</b>	Operating System	Embedded Linux	
	Storage	1 TB (up to 4TB)	1 TB (up to 4TB)
	Video Export	USB, CD/DVD RW, Network	
<b>NETWORK</b>	Connection	Ethernet	
	Protocol	LAN, DHCP, Dynamic IP, DDNS,	
	Remote Software	Web Browser(IE, Safari, Firefox), CMS, Smart Phone, iPad, Smart Phone App ( iPhone, Android)	
	Max Transmission Rate	240 fps @ CIF	480 fps @ CIF
<b>INTERFACE</b>	Audio In / Out	4 In / 1 Out	4 In / 1 Out
	Alarm In / Out	8 In/ 8 Out + 4relay out	16 In/ 16 Out + 4relay out
	PTZ CONTROL	RS485	
	USB Interface	3 x USB (Front 2, Rear 1)	
	User Interface	Front Buttons, Mouse, Remote Control, Remote Keyboard(Optional), Two-way Audio	
<b>REMOTE ACCESS</b>	Web Setting	Live Monitoring, Search, Setup, Backup	
	Device Control	PTZ control	
	Audio	Two-way audio	
<b>ETC</b>	Dimension (W x H x D)	17" x 3 1/2" x 16 1/2"	
	Operating Temperature	0°C ~ 40°C	
	Power	100 to 240 VAC / Approx. 60 watt	
	Operating Humidity	10 ~ 90%	