



HISCO SENTINEL HD NVR



1080p Full HD Network Video Recorder
 Realtime Display & Recording in HD
 Built-in PoE Switching Hub
 True Plug & Play

ADVANCED FEATURES

- 1080p HD Realtime Display & Recording
- High Definition Display with HDMI
- Built in PoE Switching HUB for Cameras
- Automatic Camera IP Configuration
- Dual Streaming
- Robust Embedded Linux OS
- iPhone, iPad and Android Phone Apps
- Free DDNS
- Auto Port Forwarding by UPnP
- Instant Timeline Search
- Thumbnail Search
- Overwrite Protection for Critical Video

HISCO SENTINEL SERIES NVR SPECIFICATIONS

Model	SEN-L412	SEN-L824	
VIDEO	Video Input	4CH(RJ45)	8CH(RJ45)
	Output	HDMI (1920 x 1080)	
	Video Compression	H.264	
RECORD & PLAYBACK	Live Display Speed	120 fps @ 1080p	240 fps @ 1080p
	Recording Rate	120 fps @ 1080p	240 fps @ 1080p
	Recording Resolution	1920 x 1080, 1280 x 720, 640 x 360	
	Recording Mode	Continuous, Event, Pre-Event (upto 5sec), Panic	
	Recording Quality	Independent channel setting: resolution, quality, frame rate	
	Search Mode	Date/Time, Calendar, Event, Thumbnail	
SYSTEM	Operating System	Embedded Linux	
	Storage	1 TB (up to 4TB)	
	Video Export	AVI or Raw Video(Multi-View) files via USB, FTP, Network	
NETWORK	Connection	Ethernet	
	Protocol	HTTP, DHCP, DDNS, WS-Discovery, RTP, RTSP, SMTP, NTP, FTP, uPNP	
	Remote Software	Web Browser(IE, Safari, Firefox), CMS, Smart Phone, iPad, Smart Phone App (iPhone, Android)	
	Security	Password Protection(3 levels), Secure LAN for IP cameras, Network Attack Protection	
	Max Transmission Rate	120 fps	
INTERFACE	Audio In / Out	1 In / 1 Out	1 In / 1 Out
	Alarm In / Out	4 (IP) + 2 (Internal) / 4 (IP)+ 1 RELAY (Internal)	8 (IP) + 2 (Internal) / 8 (IP)+ 1 RELAY (Internal)
	USB Interface	2 x USB	
	User Interface	Mouse, Remote Control, Remote Keyboard(Optional), Two-way Audio	
REMOTE	Web Setting	Live Monitoring, Search, Setup, Backup	
	Audio	Two-way audio	
ETC	Dimension (W x H x D)	305 x 44 x 298 (mm)	
	Operating Temperature	0°C ~ 40°C	
	Power	12V adaptor + 48V adaptor	
	Operating Humidity	10 ~ 90% N/C	



SEN-L412



SEN-L824

