



# Hisco alphaHDS Series HD Hybrid DVR



## ADVANCED FEATURES

- Hybrid: 2 HD and 14 Analog Cameras
- High Definition Display with HDMI
- H.264 Video Format
- Real-time Log Viewer
- Up to 8 TB Internal Storage
- Dual Streaming
- Up to 16 Cameras Simultaneous Playback
- iPhone, iPad and Android Phone Apps
- Free DDNS
- Auto Port Forwarding by UPnP
- Support for Up to 4 POS Data Recording
- Email Notification with JPG, Video Clip
- Jog Shuttle
- Powerful CMS with E-Map Function

## HISCO alphaHDS SERIES HD HYBRID DVR SPECIFICATIONS

	Model	HIS-A7214HHDS
<b>VIDEO</b>	Video Input	2 HD-SDI / 14 BNC Inputs
	Ouput	1 VGA, 1 HDMI
	Display Resolution	MAX. 1920X1080
<b>RECORD &amp; PLAYBACK</b>	Video Compression	H.264
	Live Display Speed	480 fps
	Recording Rate	420(350)fps@H.D1
	Recording Mode	Continuous, Alarm, Motion, Emergency
	Recording Quality	Super / High / Standard
	Playback Speed	X1, X2, X4, X8, X16, X32, X64, Extreme
	Archive File Format	EXE (Video Clip) / JPEG (Still Image)
<b>SYSTEM</b>	Operating System	Embedded Linux
	Multi Language	Arabic/Chinese (Traditional/Simplified)/Croatian/Czech/Danish/Dutch/English/Finnish/French German/Italian/Japanese/Korean/Persian/Polish/Portuguese/Russian/Spanish/Thai/Turkish
	Storage	1 TB (up to 8TB)
	Video Export	USB, CD/DVD RW, Network
<b>NETWORK</b>	Connection	Ethernet
	Protocol	LAN, DHCP, Dynamic IP, DDNS,
	Remote Connection	CMS, Smart Phone, iPad, Smart Phone App ( iPhone, Android)
<b>INTERFACE</b>	Audio In / Out	16 In / 1 Out
	Alarm In / Out	16 In/ 16 Out
	PTZ CONTROL	RS-485/422 Terminal Block
	USB Interface	4 Ports (2 x Front Panel, 2 x Rear Panel)
	POS Support	4
<b>REMOTE ACCESS</b>	Web Setting	Live Monitoring, Search, Setup, Backup
	Device Control	PTZ control
<b>ETC</b>	Dimension (W x H x D)	16.93" x 3.46" x 14.96"
	Operating Temperature	5°C ~ 40°C
	Power	100 to 240 VAC / Max. 95W
	Operating Humidity	10 ~ 90%