



HIS-C1122HDS

1080p HD-SDI Box Camera

ADVANCED FEATURES

- 2 Megapixel Progressive Scan CMOS sensor
- 1080p HD Video
- Day & Night
- On Screen Menu Display (OSD)
- WDR (Wide Dynamic Range)
- Uses RG-59 or RG-6 Coaxial Cable
- Privacy Mask
- Defog Function

Specifications

Camera

Image Sensor	1/3" Panasonic CMOS
Video Output	HD-SDI
Effective Pixels	1944 (H) x 1092 (V) = 2,122,848 pixels
Resolution	1920 x 1080 (1080p) 1280 x 720 (720p)
S/N Ratio	More than 50dB (AGC off)
Min. Illumination	Color: 1.0 Lux, Color : 0.002 Lux(DSS) B/W: 0.5 Lux, B/W: 0.001Lux (DSS)
Lens Control	DC/Manual
Shutter Speed	Auto/Manual (1/30-1/60000)
DSS	Off/ x2/x3/x/4
AGC	On/Off
WDR/BLC	Off/WDR/BLC
Day/Night	Auto/Day/Night/Ext
White Balance	Auto/Preset/Manul/Inddor/Outdoor
Sharpness	0 - 10 Steps
Mirror	Off/H/V/H&V
Freeze	Off/On
Defog	Off/On
DNR	Off/Low/Middle/High/Auto
Privacy Mask	Off/On (32 points)
Motion Detection	Off/On (4 points)
HD Format	1080p/720p

Electrical

Power Source	DC 12V ±10%
Power Consumption	250mA
Power Input	Connector

Mechanical & Environmental

Dimension (W x H x D)	70 mm x 55 mm x 135 mm
Weight	0.241 Kg
Operating Temperature	-10 °C to +50 °C
Storage Temperature	-10 °C to +50 °C
Humidity	0- 80 % Relative Humidity