



## ADVANCED FEATURES

- Up to 1080p Full HD Video Recording
- Full HD Display(HDMI)
- Instant Playback while Live Viewing
- Real-time Log Viewer
- H.264 Video Format
- Dual Streaming
- Simultaneous Multi Camera Playback
- iPhone, iPad and Android Phone Apps
- Free DDNS
- Auto Port Forwarding by UPnP
- Video Book Mark for Quick Archiving
- Use Existing Coaxial Cables
- Jog Shuttle
- Overwrite Protection for Critical Video

## HISCO SENTINEL SERIES HD-SDI DVR SPECIFICATIONS

Model	SEN-400HDS	SEN-800HDS	
<b>VIDEO</b>	Video Input	4 HD-SDI	8 HD-SDI
	Ouput	MAIN: 1 HDMI/1 VGA	
	Display Resolution	1920 x 1080p	
<b>RECORD &amp; PLAYBACK</b>	Video Compression	H.264 (DSP Based)	
	Live Display Speed	120 fps	240 fps
	Recording Rate	120 fps @ 1080p	120 fps @ 1080p
	Recording Mode	Continuous, Event, Pre-Event (upto 5sec), Panic	
	Recording Quality	Independent channel setting: resolution, quality, frame rate	
	Search Mode	Date/Time, Calender, Event, Multi-Zone hour	
<b>SYSTEM</b>	Operating System	Embedded Linux	
	Internal Storage	1TB (up to 4TB)	
	External Storage	e-SATA	
	Video Export	USB, CD/DVD RW, Network	
<b>NETWORK</b>	Connection	Ethernet	
	Protocol	LAN, DHCP, Dynamic IP, DDNS,	
	Remote Software	Web Browser(IE, Safari, Firefox), CMS, Smart Phone, iPad, Smart Phone App ( iPhone, Android)	
	Max Transmission Rate	120 fps @ CIF	
<b>INTERFACE</b>	Audio In / Out	4 In / 1 Out	
	Alarm In / Out	4 In/ 2 relay out	
	PTZ CONTROL	RS485	
	USB Interface	3 x USB (Front 2, Rear 1)	
	User Interface	Front Buttons, Mouse, Remote Control, Remote Keyboard(Optional), Two-way Audio	
<b>REMOTE ACCESS</b>	Web Setting	Live Monitoring, Search, Setup, Backup	
	Device Control	PTZ control	
	Audio	Two-way audio	
<b>ETC</b>	Dimension (W x H x D)	1.5U, 360 x 66 x 360 (mm)	
	Operating Temperature	0°C ~ 40°C	
	Power	DC 12V - 5A Adaptor (20W)	
	Operating Humidity	10 ~ 90%	