



HIGH DEFINITION



ADVANCED FEATURES

- Up to 1080p Full HD Video Recording
- HD-SDI Hybrid DVR
- Instant Playback while Live Viewing
- Real-time Log Viewer
- H.264 Video Format
- Dual Streaming
- Up to 16 Cameras Simultaneous Playback
- iPhone, iPad and Android Phone Apps
- Free DDNS
- Auto Port Forwarding by UPnP
- Video Book Mark for Quick Archiving
- Use Existing Coaxial Cables
- Jog Shuttle
- Overwrite Protection for Critical Video

HISCO SENTINEL SERIES HD-SDI DVR SPECIFICATIONS

Model	SEN-H4400HDS	SEN-H8800HDS		
VIDEO	Video Input	4 HD-SDI + 4 SD Analog Inputs	8 HD-SDI + 8 SD Analog Inputs	
	Ouput	MAIN: 1 HDMI/1 VGA, SPOT: 1 HDMI		
	Display Resolution	1920 x 1080p		
RECORD & PLAYBACK	Video Compression	H.264 (DSP Based)		
	Live Display Speed	240 fps	480 fps	
	Recording Rate	HD: 60 fps @ 1080p, SD: 120f ps @ D1		
	Recording Mode	Continuous, Event, Pre-Event (upto 5sec), Panic		
	Recording Quality	Independent channel setting: resolution, quality, frame rate		
	Search Mode	Date/Time, Calender, Event, Multi-Zone hour		
SYSTEM	Operating System	Embedded Linux		
	Internal Storage	1TB (up to 4TB)		
	External Storage	e-SATA		
	Video Export	USB, CD/DVD RW, Network		
NETWORK	Connection	Ethernet		
	Protocol	LAN, DHCP, Dynamic IP, DDNS,		
	Remote Software	Web Browser(IE, Safari, Firefox), CMS, Smart Phone, iPad, Smart Phone App (iPhone, Android)		
	Max Transmission Rate	240 fps @ CIF	480 fps @ CIF	
INTERFACE	Audio In / Out	8 In / 1 Out	16 In / 1 Out	
	Alarm In / Out	4 In/ 2 relay out		
	PTZ CONTROL	RS486		
	USB Interface	3 x USB (Front 2, Rear 1)		
	User Interface	Front Buttons, Mouse, Remote Control, Remote Keyboard(Optional), Two-way Audio		
	REMOTE ACCESS	Web Setting	Live Monitoring, Search, Setup, Backup	
Device Control		PTZ control		
Audio		Two-way audio		
ETC	Dimension (W x H x D)	1.5U, 360 x 66 x 360 (mm)		
	Operating Temperature	0°C ~ 40°C		
	Power	DC 12V - 5A Adaptor (20W)		
	Operating Humidity	10 ~ 90%		