



# HD-SDI Video Surveillance Solutions



## HIS-C1222HDS-V4

HD 1080p Indoor IR Dome Camera

HD-SDI, EX-SDI, HD-TVI & Analog

### Features

HD-SDI/EX-SDI/HD-TVI 1080P Vari-Focal WDR Indoor IR Dome

- HD1080P Video Output
- HD-SDI/EX-SDI/HD-TVI Technology
- OSD menu, DNR
- 80 ft IR distance
- HD video via coaxial cable
- True Wide Dynamic Range

Specifications	
Model Number	HIS-C1222HDS-V4
Image Sensor	1 / 2.9" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) x 1080(V)
Min. Illumination	0.02 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/30,000 s
Lens	2.8 ~ 12 mm @ F1.4 Angle of View: 102° ~ 35°
Angle Adjustment	Pan: 360°, Tilt: 90°, Rotation: 360°
Day & Night	ICR
Video Frame Rate	1080p @ 30fps
Video Outputs	1 x HD-SDI/EX-SDI, 1 HD-TVI/CVBS
WDR	True WDR
Privacy Mask	On / Off, maximum 16 zones

Specifications	
Motion Detection	On / Off, maximum 4 zones
Functions	Digital noise reduction, Defog, Mirror/Flip,
Working Temperature / Humidity	-10 °C ~ 60 °C (-40 °F ~ 140 °F) Humidity 90% or less (non-condensing)
Power Supply	Dual Volt: 12 VDC, 24 VAC
Power Consumption	Max. 450mA
Weather Proof Ratings	Indoor
IR Range	Up to 80 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø5.4" x 5"
Weight	1.95lbs