



IP Video Surveillance Solutions



HIS-HDXPT30E

HDmax Series 3MP IR Turret Camera

Features

3MP IR Turret, Exterior

- 3 Megapixel (2048 x 1536) Resolution
- Full HD 1080p real-time video
- True WDR & 3D DNR & BLC
- EXIR illuminator up to 100ft.
- IP66
- PoE

Specifications

Model Number	HIS-HDXPT30E
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ F1.2, AGC ON, 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm @ F2.0, angle of view: 75.8°
lens mount	M12
Angle adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR, 120db
Backlight compensation	Yes, zone configurable
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Max. image resolution	2048 x 1536
Frame rate	60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 5W (7W with ICR on)
Ingress protection	IP66
EXIR range	up to 100ft
Dimensions	127 x 97.5 mm (5"x3.8")
Weight	670g (1.5 lbs)