



# HD-TVI Video Surveillance Solutions



## HIS-HDXT22S

**HDmax** Series 1080p Vandal IR Dome Camera

### Features

HD-TVI 1080P Vandal IR Dome Camera

- HD1080P Video Output
- Adopt HD-TVI Technology
- OSD menu, DNR
- 60 ft IR distance
- IP66 weatherproof
- UTC(Up the Coax) function
- Optional UTP Balun available up to 600ft

Specifications	
Model Number	HIS-HDX22S
Image Sensor	1 / 2,7" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1930(H) x 1088(V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/50,000 s
Lens	3.6mm (2.8mm, 6mm optional), Angle of View: 80.9°(3.6mm), 103.5°(2.8mm), 54.3°(6mm)
Angle Adjustment	Pan: 360°, Tilt: 80°
Day & Night	ICR
Video Frame Rate	1080p @ 30fps
HD Video Output	1 HD-TVI output up to 1200ft with RG59U 95%
CVBS Output	N/A
Privacy Mask	On / Off, maximum 2 zones
Motion Detection	On / Off, maximum 4 zones

Specifications	
Functions	Digital noise reduction, Digital zoom(62x)
Working Temperature / Humidity	-40 °C ~ 60 °C Humidity 90% or less (non-condensing)
Power Supply	12 VDC±10%
Power Consumption	Max. 3W
Weather Proof Ratings	IP66, IK10
IR Range	Up to 60 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø 4.37" x 3.24"
Weight	1.21lbs