



HD-TVI Video Surveillance Solutions



HIS-HDXT22VSZ

HDmax Series 1080p Motorized VF Turret IR

Dome Camera

Features

HD-TVI 1080P Outdoor Motorized Vari-focal Turret IR Camera

- HD1080P Video Output
- Adopt HD-TVI Technology
- True Day/Night
- 2.8 ~ 12mm vari-focal lens
- Motorized Vari-Focal Len
- OSD menu, 3D DNR, Smart IR
- Up to 150ft IR distance
- UTC(Up the Coax) function

Specifications	
Model Number	HIS-HDXT22VSZ
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) x 1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8 ~ 12mm Motorized lens
Day & Night	ICR

Specifications	
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C ~ 60 °C Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	12V DC: Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	θ 5.1" x 4"
Weight	0.9 lb