



HD-TVI Video Surveillance Solutions



HIS-HDXT30S

HDmax Series 3MP Vandal IR Dome Camera

Features

HD-TVI 3MP Exterior IR Dome Camera

- 3MP Video Output
- HD-TVI Technology
- OSD menu, DNR
- 60 ft IR distance
- IP66 weatherproof
- Up the Coax(via coaxial cable)
- True WDR

Specifications	
Model Number	HIS-HDXT30S
Image Sensor	3MP CMOS
Signal System	PAL / NTSC
Effective Pixels	2052(H) x 1536(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/50,000 s
Lens	3.6mm (2.8mm, 6mm optional), Angle of View: 80.9°(3.6mm), 103.5°(2.8mm), 54.3°(6mm)
Angle Adjustment	Pan: 0 ~ 360°, Tilt: 0 ~ 80°
Day & Night	ICR

Specifications	
Video Frame Rate	1920 x 1536 @ 18fps
HD Video Output	1 HD-TVI output up to 1200ft with RG59U 95%
CVBS Output	N/A
AGC	support
D/N Mode	Color / BW / Smart
WDR	120dB True WDR
Working Temperature / Humidity	-40 °C ~ 60 °C (-40 °F ~ 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Weather Proof Ratings	IP66, IK10
IR Range	Up to 60 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø4.37" x3.24"
Weight	0.77lbs